

Windows®. Life without Walls™.  
Fujitsu recommends Windows 7.

# Data Sheet

## Fujitsu ESPRIMO Q900

### Desktop PC

The mini with more PC per ccm3

#### ESPRIMO Q900

A real eye-catcher on your desk and everywhere else – the extremely small, quiet and elegant ESPRIMO Q900. The versatile mini PC combines the performance of a full featured desktop PC, low power consumption and certification for ENERGY STAR®, minimal noise emission thanks to an innovative fan concept, state-of-the-art ports, such as USB 3.0, DisplayPort, DVI and an optional multi-card reader as well as system management functions in the size of a CD cover and a volume of only 1.6 liters.



#### An elegant PC for challenging tasks

Eye-catcher on every desk with a modern and exclusive design

- Fully equipped mini PC with a volume of 1.6 liters – weighing 1.4 kg

#### A black shell and a green core

The most energy-efficient computer of our ESPRIMO series reduces your energy consumption

- Intel® Mobile Technology for 13-watt power consumption in idle mode, extended power management settings and an up to 90% energy efficient AC adapter

#### Small, flexible and powerful

Intelligent performance using state-of-the-art Intel technology and high flexibility to meet all requirements

- Up to Intel® Core™i5 processor, Genuine Windows® 7 Professional, up to 8 GB memory, 500 GB hard disk drive, 5 USB 2.0 ports, 2 USB 3.0 ports, a display port and multi-card reader

#### System management

Simple system administration for complex IT infrastructures

- Intel® vPro™ technology and DeskView manageability

#### Quiet

Pleasant working environment due to an extremely quiet system

- New fan concept for even lower noise levels



# Components

<b>Processor</b>	Intel® Core™ i5-2520M processor (2 Cores / 4 Threads, 2.5 GHz, 3 MB, Intel® HD Graphics 3000) Intel® Core™ i3-2310M processor (2 Cores / 4 Threads, 2.10 GHz, 3 MB, Intel® HD Graphics 3000) * Intel® Celeron® processor B810 (2 Cores / 2 Threads, 1.60 GHz, 2 MB, Intel® HD Graphics) *Processor only for SMB, education and government
<b>Operating system</b>	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
<b>Operating system compatible</b>	openSUSE Linux Genuine Windows Vista® Genuine Windows® XP
<b>Operating system notes</b>	Microsoft Office 2010 preloaded. Purchase a Product Key to activate a full Microsoft Office 2010 suite. Limited Windows XP support. Microsoft discontinued Windows XP certification on system level.
<b>Memory modules</b>	2 GB (1 module(s) 2 GB) DDR3, non-ECC, 1333 MHz, PC3-10600, SO DIMM 4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1333 MHz, PC3-10600, SO DIMM
<b>Hard disk drives (internal)</b>	SSD SATA, 128 GB, 2.5-inch, full disk encryption SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. SATA II, 5400 rpm, 500 GB, 2.5-inch* SATA II, 5400 rpm, 320 GB, 2.5-inch* SATA, 5400 rpm, 250 GB, 2.5-inch
<b>Hard disk notes</b>	*Disk imaging software of the customer must be 4k sector size / advanced format ready Up to 18 GB of HDD space is reserved for system recovery
<b>Drives (optional)</b>	Card Reader 6-in-1 ESPRIMO Q DVD Super Multi Slot-in slim
<b>Interface add on cards/components (optional)</b>	WLAN 2x2 agn Bluetooth Q900
<b>Base unit</b>	ESPRIMO Q900
<b>Mainboard</b>	
<b>Formfactor</b>	proprietary
<b>Chipset</b>	Intel® QM67
<b>Processor socket</b>	rPGA 989A/B
<b>Processor quantity maximum</b>	1
<b>Memory slots</b>	2 SO DIMM (DDR3, 1333 MHz)
<b>Memory frequency</b>	1333 MHz
<b>Memory notes</b>	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same In configurations with 4 GB the visible memory may be reduced to approximately 3.5 GB or less (for 32 bit operating systems, depending on system configuration)
<b>LAN</b>	10/100/1000 MBit/s Intel® 82579 LM
<b>Integrated WLAN</b>	1 (optional)
<b>BIOS version</b>	AMI Aptio 4.6

**Mainboard**

<b>BIOS features</b>	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
<b>Audio codec</b>	Realtek ALC662
<b>Audio features</b>	Support of high-definition audio for S/PDIF output with up to 5.1 channels

**I/O controller on board**

<b>Serial ATA total</b>	1
<b>Controller functions</b>	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI

**Interfaces**

<b>Audio: line-in</b>	1
<b>Audio: line-in / microphone</b>	1
<b>Audio: line-out / headphones / SPDIF</b>	1 (optical)
<b>USB 2.0 total</b>	5
<b>USB 3.0 total</b>	2
<b>USB front</b>	2
<b>USB rear</b>	5
<b>VGA</b>	1 (via DVI to VGA adapter)
<b>DisplayPort</b>	1
<b>DVI</b>	DVI-I
<b>Ethernet (RJ-45)</b>	1
<b>Kensington Lock support</b>	1
<b>Interface Module notes</b>	Anytime USB charge functionality

**Input device / components**

	Optical USB tilt wheel mouse
--	------------------------------

**Drive bays**

<b>Drive bays total</b>	2
<b>2.5-inch bays</b>	1
<b>5.25-inch external bays</b>	1
<b>Drive bay notes</b>	slim slot-in

**Graphics on board**

<b>Graphics brand name</b>	Intel® HD Graphics or HD Graphics 3000 (depending on CPU)
<b>Shared video memory</b>	up to 1759 MB
<b>Refresh rate 1024 x 768 (recommended / max.)</b>	- / -
<b>Refresh rate 1280 x 1024 (recommended / max.)</b>	- / -
<b>Refresh rate 1600 x 1200 (recommended / max.)</b>	- / -
<b>TFT resolution (VGA)</b>	1024 x 768 pixel 1280 x 1024 pixel 1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1600 x 1200 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel

**Graphics on board**

<b>TFT resolution (DVI)</b>	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
<b>TFT resolution (DisplayPort)</b>	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel 2560 x 1440 pixel 2560 x 1600 pixel
<b>Graphics features</b>	DirectX® 10.1 support HDCP support Dual display support OpenGL® 2.1
<b>Graphics notes</b>	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

**Electrical values**

<b>Power efficiency note</b>	power supply efficiency (at 230V; 20% / 50% / 100% load) : 87% / 90% / 87%
<b>Operating voltage range</b>	100 V - 240 V (AC Input)
<b>Operating line frequency range</b>	47 Hz - 63 Hz
<b>Max. output of single power supply</b>	external (90W)

**Power consumption**

<b>Power consumption note</b>	See white paper Energy Consumption
<b>Link to Energy White Paper</b>	<a href="http://docs.ts.fujitsu.com/dl.aspx?id=ca024c84-ccb4-459f-b9eb-b5fb049daa11">http://docs.ts.fujitsu.com/dl.aspx?id=ca024c84-ccb4-459f-b9eb-b5fb049daa11</a>

**Heat dissipation**

<b>Heat dissipation notes</b>	See white paper Energy Consumption
-------------------------------	------------------------------------

**Noise for standard configuration (HDD, ODD)**

<b>Noise emission</b>	According to ISO9296
<b>Related Processors for noise</b>	Intel® Core i5-2540M
<b>Noise Operation mode 1: ODD load (Blue angel requirement)</b>	4.7 B / 33.5 dB(A)
<b>Noise Operation mode 2: HDD load (Blue angel requirement)</b>	3.2 B / 18.5 dB(A)
<b>Noise Operation mode 3: CPU 90% load (Blue angel requirement)</b>	4.8 B / 34 dB(A)
<b>Noise Operation mode 4: High load</b>	4.8 B / 34.4 dB(A)
<b>Noise Operation mode 5: Office applications</b>	3.3 B / 18.4 dB(A)
<b>Noise notes / description</b>	Noise for standard configuration CPU, HDD, ODD; A weighted sound power level L <sub>wad</sub> (in B) / Workplace related A-weighted sound pressure level L <sub>pAm</sub> (in dB(A)), (bystander position) (ISO9296)

**Dimensions / Weight / Environmental**

<b>Dimensions (W x D x H)</b>	165 x 168 x 57 mm
<b>Operating position</b>	Backpack solution (optional)
<b>Weight</b>	approx. 1.4 kg
<b>Weight notes</b>	Actual weight may vary depending on configuration
<b>Operating ambient temperature</b>	5 - 35°C

**Compliance**

<b>Product</b>	ESPRIMO Q900
<b>Model</b>	MPC-D1009
<b>Germany</b>	Blauer Engel / Blue Angel in progress
<b>Europe</b>	CE Nordic Swan in progress EN 60601-1-2
<b>Global</b>	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® EPEAT® in progress
<b>Compliance link</b>	<a href="https://sp.ts.fujitsu.com/sites/certificates/default.aspx">https://sp.ts.fujitsu.com/sites/certificates/default.aspx</a>

**Additional Software**

<b>Additional software (preinstalled)</b>	Nero Essentials S (burning software) Fujitsu Recovery (Hard Disk Based Recovery)
<b>Additional software (optional)</b>	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) Nero 9 Essentials XL CyberLink PowerDVD BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive / Blu-ray playback is not supported under Windows XP if the system runs on Intel onboard graphics)

**Manageability**

<b>Manageability features</b>	PXE 2.1 Boot code Wake up from S5 (off mode) iAMT 7.0 DeskUpdate Driver management
<b>Manageability type</b>	DeskView 10.x client management including: DASH 1.1 remote system management
<b>DeskView features</b>	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)
<b>Manageability link</b>	<a href="http://ts.fujitsu.com/manageability">http://ts.fujitsu.com/manageability</a> <a href="http://www.altiris.com/fujitsu">http://www.altiris.com/fujitsu</a> <a href="http://ts.fujitsu.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html">http://ts.fujitsu.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html</a>

**Security**

<b>Physical security</b>	Kensington Lock support
<b>System security</b>	Write protect option for the Flash EPROM Embedded security (TPM 1.2) Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
<b>User security</b>	User and supervisor BIOS password Hard disk password Optional: Access protection via external SmartCard reader

**Packaging information**

<b>Packaging dimension</b>	395x198x284 mm
<b>Max. quantity / pallet</b>	48
<b>Material - Weight (g) Carton</b>	670g
<b>Material - Weight (g) EPS / PS</b>	appr. 10 g

---

**Packaging information**

Material - Weight (g) PE	appr. 125 g
Packaging notes	printed user documentation is bleached in chlorin free process

---

**Warranty**

Standard Warranty	3 years
Service level	Bring-In / On-Site Service (depending on country)

**Maintenance and Support Services - the perfect extension**

Recommended Service	5x9, Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	<a href="http://ts.fujitsu.com/Supportservice">http://ts.fujitsu.com/Supportservice</a>

## More information

### Fujitsu platform solutions

In addition to Fujitsu ESPRIMO Q900, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

#### Computing Products

[www.fujitsu.com/global/services/computing/](http://www.fujitsu.com/global/services/computing/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about Fujitsu ESPRIMO Q900, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
<http://ts.fujitsu.com/ESPRIMO>

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



### Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.  
For further information see [http://ts.fujitsu.com/terms\\_of\\_use.html](http://ts.fujitsu.com/terms_of_use.html)  
Copyright © Fujitsu Technology Solutions

### Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

#### Contact

FUJITSU Technology Solutions  
Website: <http://ts.fujitsu.com>  
2011-03-01 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.  
For further information see [http://ts.fujitsu.com/terms\\_of\\_use.html](http://ts.fujitsu.com/terms_of_use.html)  
Copyright © Fujitsu Technology Solutions