

Fujitsu recommends Windows® 7.

# Data Sheet

## Fujitsu ESPRIMO Q910

### Desktop PC

The Mini with More PC per cm

The Fujitsu ESPRIMO Q910 delivers excellent performance, energy efficiency and manageability in a mini PC. An Intel® Core™ processor and Intel® vPro™ technology deliver professional computing and management. Its stylish design is also practical, with two front USB 3.0 ports for lightning fast connections

#### An elegant mini PC for the modern office environment

Eye-catcher on your desk with a modern and exclusive design

- Fully equipped mini PC with a volume of 1.9 liters - a true member of our Fujitsu ESPRIMO Desktop family now based on Desktop technology

#### Black shell and a green core

The most energy-efficient computer of our Fujitsu ESPRIMO family cuts your energy bill and helps to save your budget

- Smart Desktop Technology for lowest power consumption in idle mode, optional PVC free system and an 90% energy efficient onboard power supply, halogen free mainboard

#### Unleash the power

Latest Intel® technology to support your challenging business applications

- 3rd generation Intel® Core™ processor family

#### Sophisticated system management


Simple system administration in complex IT infrastructures

- Intel® vPro™ technology (depending on processor) and Fujitsu DeskView manageability

#### Flexible operations and easy upgrade of the system

Pleasant working environment due to a tidy desk

- Horizontal or vertical operations and an integrated VESA mount, service door for easy upgrade of major components



# Components

	Intel® vPro™ Logo with Intel® Core i5 processors *with Intel® Turbo Boost Technology (clock speed and will vary depending on workload and other variables)
<b>Processor</b>	Intel® Core™ i5-3470T processor (2 Cores / 4 Threads, up to 3.60 GHz 2.90 GHz, 6 MB, Intel® HD Graphics 2500) * Intel® Core™ i3-2120T processor (2 Cores / 4 Threads, 2.60 GHz, 3 MB, Intel® HD Graphics 2000) Intel® Pentium® processor G640T (2 Cores / 2 Threads, 2.40 GHz, 3 MB, Intel® HD Graphics) Intel® Celeron® processor G540T (2 Cores / 2 Threads, 2.10 GHz, 2 MB, Intel® HD Graphics)
<b>Operating systems</b>	
<b>Operating system</b>	Windows® 7 Home Basic (EM) 32-bit Windows® 7 Home Premium 64-bit Windows® 7 Professional 32-bit Windows® 7 Professional 64-bit
<b>Operating system compatible</b>	Windows® XP
<b>Operating system notes</b>	Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via <a href="http://support.ts.fujitsu.com">http://support.ts.fujitsu.com</a>
<b>Memory modules</b>	2 GB (1 module(s) 2 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM 4 GB (1 module(s) 4 GB) DDR3, non-ECC, 1600 MHz, PC3-12800, SO DIMM
<b>Hard disk drives (internal)</b>	SSD SATA III, 256 GB, 2.5-inch SSD SATA III, 128 GB, 2.5-inch HDD SATA II, 7200 rpm, 320 GB, 2.5-inch HDD SATA II, 7200 rpm, 160 GB, 2.5-inch, S.M.A.R.T. HDD SATA II, 5400 rpm, 750 GB, 2.5-inch* HDD SATA II, 5400 rpm, 500 GB, 2.5-inch* HDD SATA II, 5400 rpm, 250 GB, 2.5-inch*
<b>Hard disk notes</b>	*Disk imaging software of the customer must be 4k sector size / advanced format ready Up to 18 GB of HDD space is reserved for system recovery
<b>Graphics add on cards (optional)</b>	DP to DVI-D (single link) Adapter Cable
<b>Drives (optional)</b>	BD Triple Writer SATA Slot-in slim DVD Super Multi Slot-in slim
<b>Interface add on cards/components (optional)</b>	
	WLAN 802.11 b/g/n (2x2) and Bluetooth
<b>Base unit</b>	ESPRIMO Q910
<b>Mainboard</b>	
<b>Mainboard type</b>	D3183
<b>Formfactor</b>	proprietary
<b>Chipset</b>	Intel® Q77
<b>Processor socket</b>	LGA 1155
<b>Processor quantity maximum</b>	1
<b>Memory slots</b>	2 SO DIMM (DDR3, 1600 MHz)
<b>Supported capacity RAM (max.)</b>	16 GB
<b>Memory frequency</b>	1600 MHz
<b>Memory notes</b>	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same
<b>LAN</b>	10/100/1000 MBit/s Intel® 82579 LM
<b>Integrated WLAN</b>	1 (optional)
<b>BIOS version</b>	AMI Aptio 4.6

**Mainboard**

BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio codec	Conexant CX20642
Audio features	High Definition audio, 5.1 surround sound, Buzzer

**I/O controller on board**

Serial ATA total	2
thereof SATA III	2
Controller functions	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI

**Interfaces**

Audio: line-out / headphone	1
Audio: line-in / microphone	1
USB 2.0 total	3
USB 3.0 total	4
USB front	2x 3.0
USB rear	2x 2.0 and 2x 3.0
VGA	1 (via DVI to VGA adapter, part of shipment)
DisplayPort	1
DVI	1 (DVI-I)
Ethernet (RJ-45)	1
Kensington Lock support	1
Multicardreader	1
Interface Module notes	Anytime USB charge functionality

**Input device / components**

	Optical USB wheel mouse
Input devices (optional)	KBPC PX ECO Mouse M440 ECO

**Drive bays**

Drive bays total	2
2.5-inch internal bays	1
5.25-inch external bays	1
Drive bay notes	slim slot-in

**Graphics on board**

Graphics brand name	Intel® HD Graphics, HD Graphics 2000, HD Graphics 2500, HD Graphics 4000 (depending on CPU)
Shared video memory	up to 1759 MB
TFT resolution (VGA)	1024 x 768 pixel 1280 x 1024 pixel 1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1600 x 1200 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel

**Graphics on board**

<b>TFT resolution (DisplayPort)</b>	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel 2560 x 1440 pixel 2560 x 1600 pixel
<b>Graphics features</b>	Dual display support DirectX® 10.1 or DirectX® 11 (depending on CPU) HDCP support Open GL® 3.1 (depending on CPU) Open CL™ 1.1 (depending on CPU)
<b>Graphics notes</b>	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

**Electrical values**

<b>Power efficiency note</b>	power supply efficiency (at 115V/230V; 10% / 20% / 50% / 100% load) : 83% / 87% / 90% / 88%
<b>Rated voltage range</b>	100 V - 240 V
<b>Rated frequency range</b>	50 Hz - 60 Hz
<b>Operating voltage range</b>	90 V - 264 V
<b>Operating line frequency range</b>	47 Hz - 63 Hz
<b>Max. output of single power supply</b>	65 W (integrated in system)
<b>Power factor correction/active power</b>	No (meets input harmonic current according EN61000-3-2)
<b>Monitor outlet</b>	No

**Power consumption**

<b>Power consumption note</b>	See white paper Energy Consumption
-------------------------------	------------------------------------

**Heat dissipation**

<b>Heat dissipation notes</b>	See white paper Energy Consumption
-------------------------------	------------------------------------

**Noise emission**

<b>Related Processors for noise</b>	Intel® Core™ i5 3470T
<b>Standard noise emission</b>	2x2 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
<b>Standard noise notes / description</b>	A weighted sound power level L <sub>wad</sub> (in B) / Workplace related A-weighted sound pressure level L <sub>pAm</sub> (in dB(A))
<b>Standard noise operation mode: CPU 50% load</b>	4.7 B / 31 dB(A) Bystander ; 34 dB(A) Operator position
<b>Standard noise operation mode: HDD load</b>	3.3 B / 20 dB(A) Bystander ; 22 dB(A) Operator position
<b>Standard noise operation mode: Idle mode</b>	SSD: no noise emission, 2.5" HDD: 3.1 B / 19 dB(A) Bystander ; 21 dB(A) Operator position
<b>Standard noise operation mode: ODD load</b>	4.7 B / 33 dB(A) Bystander ; 34 dB(A) Operator position
<b>Standard noise operation mode: Office applications 2.0</b>	SSD: no noise emission, 2.5" HDD: 3.2 B / 19 dB(A) Bystander ; 21 dB(A) Operator position
<b>Blue angel noise emission according certification</b>	for max. possible configuration According to ISO 7779:2010, ECMA-74
<b>Blue angel noise notes / description</b>	A weighted sound power level L <sub>wad</sub> (in B); 1B = 10dB
<b>Blue angel noise operation mode: HDD load</b>	3.3 B = 33 dB
<b>Blue angel noise operation mode: Idle mode</b>	3.1 B = 31 dB
<b>Blue angel noise operation mode: ODD load</b>	4.7 B = 47 dB

**Dimensions / Weight / Environmental**

<b>Dimensions (W x D x H)</b>	185 x 188 x 54 mm 7.29 x 7.41 x 2.13 inch
<b>Operating position</b>	Vertical / horizontal (no feet needed)
<b>VESA mount</b>	integrated (100mm), additional mounting kit for specific monitors optional
<b>Weight</b>	1.6 kg
<b>Weight (lbs)</b>	3.53 lbs
<b>Weight notes</b>	Actual weight may vary depending on configuration
<b>Operating ambient temperature</b>	10 - 35°C (50 - 95°F)

**Compliance**

<b>Product</b>	ESPRIMO Q910
<b>Model</b>	MPC2
<b>Europe</b>	CE Nordic Swan in progress
<b>USA/Canada</b>	FCC Class B cCSAus
<b>Global</b>	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 5.0 (dedicated regions) EPEAT® Gold (dedicated regions)
<b>Compliance notes</b>	This product is free of polyvinyl chloride (PVC) when ordered with the optional PVC free power cord
<b>Compliance link</b>	<a href="https://sp.ts.fujitsu.com/sites/certificates/">https://sp.ts.fujitsu.com/sites/certificates/</a>

**Additional Software**

<b>Additional software (preinstalled)</b>	Nero Essentials S (burning software) Fujitsu Recovery (Hard Disk Based Recovery) Norton Internet Security (incl. Firewall) 60 days version Microsoft® Office Starter: reduced-functionality Word and Excel® only, with advertising. No PowerPoint® or Outlook®. Buy Office 2010 to use the full-featured software.
<b>Additional software (optional)</b>	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive / Blu-ray playback is not supported under Windows XP if the system runs on Intel onboard graphics) Nero 10 Essentials XL

**Compatibility (references)**

DMI 2.0  
PC 2001  
WMI 1.5  
USB 2.0  
SMBIOS

**Manageability**

<b>Manageability technology</b>	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) iAMT 8.0 (depending on CPU) WoL (Wake on LAN)
<b>Manageability software</b>	DeskView Client DeskView Instant BIOS Management DeskView Integration for Symantec Management Platform
<b>DeskView components</b>	Inventory Management BIOS Management Driver Management Security Management Alarm Management

**Manageability**

Manageability link	<a href="http://ts.fujitsu.com/manageability">http://ts.fujitsu.com/manageability</a>
--------------------	---

**Security**

System protection	Kensington Lock support Optional: Intrusion switch Housing Lock Plate (to use with Kensington lock)
-------------------	---

Audit proof protection	EraseDisk (optional) Boot sector virus protection Write protect option for the Flash EPROM Embedded security (TPM 1.2) Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
------------------------	---

Access protection	User and supervisor BIOS password Hard disk password Optional: Access protection via external SmartCard reader
-------------------	--

**Packaging information**

Packaging dimension (mm)	395 x 198 x 284 mm
Packaging dimension (inch)	15.55 x 7.8 x 11.18 inch
Max. quantity / pallet	48
Material - Weight (g) Carton	670 g
Material - Weight (lbs) Carton	1.48 lbs
Material - Weight (g) EPS / PS	10 g
Material - Weight (lbs) EPS / PS	0.02 lbs
Material - Weight (g) PE	125 g
Material - Weight (lbs) PE	0.28 lbs
Packaging notes	printed user documentation is bleached in chlorin free process

**Warranty**

Standard Warranty	3 years
Service level	Bring-In / On-Site Service (depending on country)

**Maintenance and Support Services - the perfect extension**

Recommended Service	5x9, Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	<a href="http://www.fujitsu.com/fts/services/support/index.html">http://www.fujitsu.com/fts/services/support/index.html</a>

## More information

### Fujitsu platform solutions

In addition to Fujitsu ESPRIMO Q910, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure-as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

#### Computing Products

[www.fujitsu.com/global/services/computing/](http://www.fujitsu.com/global/services/computing/)

#### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

### More information

Learn more about Fujitsu ESPRIMO Q910, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/fts/ESPRIMO](http://www.fujitsu.com/fts/ESPRIMO)

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



### Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)

Copyright © Fujitsu Technology Solutions

### Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

#### CONTACT

FUJITSU Technology Solutions  
Website: <http://ts.fujitsu.com>  
2012-05-31 CE-EN

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see [www.fujitsu.com/terms](http://www.fujitsu.com/terms)  
Copyright © Fujitsu Technology Solutions